

IN THE WOODS- **ALEX CARVER** NORTHERN TIMBERS CONSTRUCTION



RIVER VIEWTOM LEBOEUF
NORTHEAST CRAFTSMEN GROUP
AND H.J. LEBOEUF INC.



LAKE DUNMOREJARED MOATS
STRUCTURAL ENERGY
CORPORATION

JEAN TERWILLIGER, ARCHITECT
VERMONT INTEGRATED ARCHITECTURE, P.C., MIDDLEBURY, VT



THREE HIGH-PERFORMANCE HOMES, THREE APPROACHES

PRESENTATION GOALS

BASIC PERFORMANCE TARGETS OF HIGH PERFORMANCE HOME DESIGN

ELEMENTS OF A HIGH PERFORMANCE ENVELOPE SYSTEM

- COMPARE PERFORMANCE, COST AND CONSTRUCTABILITY
- CONSTRUCTION CHALLENGES AND TRADE-OFFS

DESIGN ELEMENTS FOR UNIQUE HIGH PERFORMANCE HOMES

- FITTING SITES
- MEETING CLIENTS' NEEDS, PERSONALITIES AND LIFESTYLES

COMMON FEATURES & GOALS

SMALL LOTS WITH NEIGHBORS

INDOOR/ OUTDOOR CONNECTION TO LAND

FULL TIME RESIDENCES FOR EMPTY NESTERS OR RETIREES

DESIRE FOR OPEN LIVING SPACE

NEED FOR OFFICE/STUDY/STUDIO ENTRY/MUDROOM

POTENTIAL FOR SINGLE LEVEL LIVING

MINIMIZE ENERGY AND MAINTENANCE COSTS

HELP COMBAT CLIMATE CHANGE



EFFICIENCY VERMONT HIGH PERFORMANCE HOME SUMMARY

ENVELOPE:

R-30 BASEMENT WALLS AND UNDER SLAB

R-40 WALLS

R-40 EXPOSED FLOORS

R-60 CEILINGS- FLAT OR SLOPED

R-5 WINDOWS (MAX U= .21)

R-4 DOORS

1 ACH50 MAX. BLOWER DOOR RESULT

HIGH PERFORMANCE HOME ELEMENTS

EFFICIENCY VERMONT HIGH PERFORMANCE HOME SUMMARY


SYSTEMS:

- EFFICIENT HEAT RECOVERY VENTILATION
- HEAT PUMP or ENERGY STAR RATED HEATING SYSTEM
- HEAT PUMP HOT WATER HEATER or ELECTRIC HOT WATER WITH DRAIN WATER HEAT RECOVERY
- ENERGY STAR APPLIANCES
- 95% ENERGY STAR LED AND/OR CFL LIGHTING

HIGH PERFORMANCE HOME ELEMENTS













Program:

Home and yoga studio

Small lot .4 acres
Sun and Privacy
2 BR
Place to write
Desire for angle in design
Cathedral ceiling




























HVAC:

2 pair Lunos E2 and bathroom fans2 heat pump headsSmall woodstove with dedicated outdoor airElectric hot water heater with drainwater heat recovery

HERS: 42

(Home Energy Rating System)

Square Feet: 1254 sf. Volume: 12645 cu. ft.

Blower Door: 155 cfm50, .74 ACH50

Predicted Energy Use:

31.2 MMBtu,

5.9 MMBtu heating, \$1500

Energy Use:

26 MMBtu, 20.7 kbtu/sf/yr, \$1260, 6905 kwh/yr electric, 1/10 cord wood



EVELOPE SYSTEMS:

Foundation:

Concrete footing and ICF frost wall for 4' grade change Extra interior insulation

Slab on grade- 8" EPS under 4" concrete

Arctic wall:

2x4 at 24" oc

OSB sheathing (taped as air barrier)

9 1/2" continuous I-joists

Cellulose outer contained by Mento Plus water barrier


Mineral wool in mechanical cavity

Corrugated metal siding

Roof:

16" I-joist with dense pack celluloseIntello inner vapor/ air control layer1 1/2" strapping with mineral wool batt,2x4 framing above sheathing for vent cavity and eaves;Standing seam metal roof

Stick framed entry and screen porch







IN THE WOODS - CONSTRUCTION

ARCTIC WALL COMPONENTS

2 x 4 frame
OSB Sheathing
2x for Bucks







Double wall spans several floors

Bulk of insulation outside the air barrier

Vented siding





Interior Roxul insulation or Damp spray

External & Internal chase and mechanicals

Expedites building process







- R-60 Roof
- Continuous vapor barrier
- Cold roof assembly
- Overhangs









- Inbound/Outbound window placement
- Window buck & air sealing
- Weep holes















RIVER VIEW - DESIGN










Program:

Traditional farmhouse
Single level living potential
Garage connection
River views
Walk-out basement to accommodate slope























ENVELOPE SYSTEMS:

Foundation:

8" (R-30) EPS under 4" concrete slab

Concrete footing/ foundation wall with 2" XPS

Wall:

2x4 stud with R-20 batt insulation

Double stud wall with airtight drywall

Dense pack cellulose

Rigid insulation w/ spray foam at rim joists

Taped plywood sheathing with Mento membrane WRB

Strapping

Hardi prefinished clapboard siding

Roof:

Raised heel truss with 6' or 9' plate height

Intello vapor/air control layer

Loose blown cellulose

Stick framed screen porch

<u>HVAC:</u>


Venmar HRV (156 cfm) with 6" metal duct

5 heat pump heads w/ 1 outdoor compressor

Woodstove

Heat pump hot water heater

Bathroom electric radiant floors under tile



HERS: 33, 12 after PV

(Home Energy Rating System)

Net-Zero operation predicted.

Square Feet: 3756 sf w/basement, Volume: 31021 cu ft

Blower Door: 203 cfm50, .4 ACH50

Predicted energy use:

48.8MMBtu/yr w/o PV production (\$2237),

20.2 MMBtu (\$1000) with 6.6kw PV production

Actual Energy Use:

51 MMBtu/yr, 15-17 kbtu/sf/yr,

Electric: 5070* kwh, \$1200

1.5-2 cord wood (20 MMBtu/cord),

*Estimated Electrical use and PV production. Less than 1yr of

use.






RIVER VIEW - CONSTRUCTION

Keep poly flat to ensure tape adherence

Find the easiest method





Keep poly down until roof is on

Cut poly as close to sheathing as possible



Try to create flat surfaces for ease of taping













Go over install procedures thoroughly





Air tight drywall method can work well Caulking Can spray foam






Figure out roof panel layout with pv layout/roof penetrations in advance



Help out mechanical/plumbing contractors

Options on duct work









LAKE DUNMORE - DESIGN
















Program:

Home and professional studio
Option for air b-n-b rental
Living space on upper level to improve lake views
Desire for cathedral ceiling space















LAKE DUNMORE LIVING SPACE













ENVELOPE SYSTEMS:

Foundation:

Concrete footing/ foundation wall with 2" XPS 2x4 stud batt insulation, 8" EPS under 4" concrete slab


Wall:

Double stud wall with airtight drywall
Dense pack cellulose outer
Mineral wool in inner stud bay
Rigid insulation spray foam rim joists
Zip sheathing, taped
Corrugated metal siding

Roof:

Scissors trusses, various plate heights Intello vapor/air control layer Loose blown cellulose

Stick framed screen porch



HERS: 44

(Home Energy Rating System)

Square Feet: 1790 sf w/studio, Volume: 15987

cu. ft.

Blower Door: 155 cfm50, .58 ACH50

Predicted energy use:

45.4 MMBtu, 21.9 MMbtu heating

\$2172

Actual Energy Use:

Electric: 9580 kwh/yr, \$1683

Propane: 200 gal., \$650

32.84 MMBtu, 18.4 kbtu/sf/yr

Moisture monitoring- 5 locations, recorded very stable at 8-16% moisture







LAKE DUNMORE - CONSTRUCTION









































HVAC:

3 pair Lunos E2 HRV (60 cfm max.)
Bath fans
3 heat pump heads
Master bathroom electric towel warmer,
Gas fireplace
Heat pump hot water heater













WALL ASSEMBLY COST COMPARISON

Arctic Wall- R-48	Double stud wall- R-43				Double stud w/ service cavity- R-44					
2x4 wall w/ 9 1/2" I-joists			2x4 wall	2x6 wall(30% increase)		2x4 wall	2x6 wall(30% inc		II(30% increase)	
Plates	\$	315.20	\$	315.20	\$	409.76	\$	315.20	\$	409.76
Studs	\$	1,255.50	\$	1,255.50	\$	1,632.15	\$	1,255.50	\$	1,632.15
Headers	\$	419.00	\$	-	\$	419.00	\$	-	\$	419.00
Window and door bucks	\$	449.65	\$	250.00	\$	-	\$	450.00	\$	-
Insulation at window jamb	\$	450.00	\$	-			\$	-		
Sheathing	\$	1,125.00			\$	1,867.50			\$	1,867.50
Strapping	\$	1,012.00	\$	-	\$	1,012.00	\$	-	\$	1,012.00
Insulation	\$	7,741.00			\$	6,780.00	\$	7,741.00		
Air sealing- membrane and tape	\$	4,200.00	\$	4,200.00			\$	4,200.00		
ונד	\$	2,024.00								
			\$	6,020.70	\$	12,120.41	\$	13,961.70	\$	5,340.41
Total	\$	18,991.35			\$	18,141.11			\$	19,302.11

Note: Numbers do not include framing or air sealing labor

CLOSING THOUGHTS:

- HIGH PERFORMANCE BUILDINGS MAKE BEAUTIFUL HOMES! THEY DO TAKE MORE PLANNING.
- ONE PERSON SHOULD TAKE RESPONSIBILITY FOR AIR SEALING!
- YES, DO TRY THESE IDEAS IN YOUR OWN PROJECTS!
- WE SHAPE OUR BUILDINGS, THEREAFTER THEY SHAPE US.- WINSTON CHURCHILL
- USE HIGH PERFORMANCE CONSTRUCTION, YOUR CLIENTS WILL BE WARM AND HAPPY CUSTOMERS!



THANK YOU! QUESTIONS?



IN THE WOODS-ALEX CARVER NORTHERN TIMBERS CONSTRUCTION




RIVER VIEWTOM LEBOEUF
NORTHEAST CRAFTSMEN GROUP
AND H.J. LEBOEUF INC.



LAKE DUNMOREJARED MOATS
STRUCTURAL ENERGY
CORPORATION

JEAN TERWILLIGER, ARCHITECT
VERMONT INTEGRATED ARCHITECTURE, P.C., MIDDLEBURY, VT





- R-30 at slab edge
- Kerf in Blueboard
- Visible reference line for slab pour

